

Six-Shooter™ Youth Training Goal

1. **STEEL HANG-ON STRUCTURE** – Structure shall be constructed of 3/4”x 3/4” square 16 ga. tubing. Structure shall be configurable so that 6 various rim heights can be achieved (6 ½’, 7’, 7 ½’, 8’, 8 ½’ & 9’) when hung from a standard 10’ high rim. Structure shall be secured to 10’ high rim by means of a safe and easy crank handle that will not “back-drive” when tightening or releasing for easy one-person setup. Handle shall be permanently secured to unit and stow behind backboard during play. Structures that secure via means of a “spring-lock” handle are not considered equal.
2. **BACKBOARD** - Constructed of 1/4” thick white ABS. Border and shooter’s square markings shall be machined into the face of the backboard to prevent marking “wear-off” common with other screen-printed backboards. Backboard shall be rectangular in shape and overall backboard size shall be approximately 48” wide and 39” high.
3. **GOAL DESIGN** – Rim shall consist of an official sized 5/8” diameter steel ring. Netlock system shall be of a continuous type so as to reduce netlock breakage common with individually welded netlocks. The rim shall be of institutional quality with all structural components being no less than 3/16” thick. A 3/16” diameter ring support shall strengthen around 60% of the bottom of the ring. Rim shall be punched to provide quick attachment to backboard for both playing and storage positions by means of an included “T-Handle.” Rim shall have an orange powdercoat finish and include a heavy-duty nylon net.
4. **WARRANTY** – Entire system shall carry a Lifetime Limited Warranty. Shipping weight shall be approximately 55#.